



PoE Easy 24 Port PoE Switch

Part Number – YSBSC03654



PoE Easy 24port PoE switch is Power Over Ethernet, which refers to the transmission of data signals to some IP-based terminals such as IP phones, Wireless Access Points (WAP), network cameras, etc. it also provides DC power. Devices that receive DC power are called powered devices.

24-Ports x 10/100/1000M and 90W Power Switch, using high-quality high-speed network IC and the most stable PoE chip. PoE ports support 802.3af/at/bt standard. This series of PoE Switch provide seamless connectivity for 10/100/1000M Ethernet; the PoE power port can automatically detect and power the devices that comply with the IEEE802.3af (15W), IEEE802.3at(30W) or IEEE802.3bt(90W) standards. Any non-PoE device intelligently detects no power and only transmits data.

With simple convenient installation and maintenance methods and rich business features, it helps users to build a safe and reliable high-performance network. It is mainly located in the core or convergence layer of user networks such as industrial parks, buildings, factories, government agencies, and residential broadband; it can be widely used in Ethernet access scenarios such as small and medium-sized enterprises, Internet cafes, hotels, and schools.



Product description

Main Feature

- 24*10/100/1000M POE Ports + 1*100/1000M Ethernet Uplink Port + 1*1.25G SFP Uplink Ports
- PoE Ports Support IEEE802.3af or IEEE802.3at or IEEE802.3bt Self-Adaptive, max 2160W output
- Ethernet Port supports 10/100/1000M adaptive and PoE functions
- PoE Port Support 90w Power Output, Max 2160W
- Support port auto flip (Auto MDI/MDIX)
- Support link monitoring, abnormal self-test and recovery
- Flow Control: IEEE 802.3x for Full-duplex Mode, Back pressure for half-duplex Mode
- Lightning protection, Surge: General Mode 6KV, Differential Mode 4KV, ESD: 8KV
- Support 1U Rack Mount Installation

Application Environment

Metropolitan Optical Broadband Network

Telecommunications, cable TV, network system integration, etc., according to network operators

Broadband Private Network

Applicable to industry, finance, government, petroleum, railway, electric power, public security, transportation, education, etc.

Multimedia Transmission

Comprehensive transmission of images, voice, data, suitable for remote teaching, conference TV, videophone and other applications

Real-time monitoring

Simultaneous transmission of real-time control signals, images, and data

Packaging Information

- Eco Friendly
- Plastic free
- 100% Recycled material
- Water based printed links on packaging
- Packing demension 481 x 258 x 83mm

© PRYSMIAN GROUP 2021, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian. The information is believed to be correct at the time of issue. Prysmian reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorized by Prysmian.